Total No.	of Questions—12]	[Total No. of	Printed Pages—5			
Seat No.			[5252]-506			
S.E. (Civ	il Engineering) (Second	l Semester) EXAN	IINATION, 2017			
FLUID MECHANICS—I						
(2015 PATTERN)						
Time : 1	wo Hours		um Marks : 50			
<i>N.B.</i> :—	(i) Answer any six que	stions from Q. No.	1 or 2 , Q. No.			
3 or 4, Q. No. 5 or 6, Q. No. 7 or 8, Q. No. 9 or 10,						
	Q. No. 11 or 12.		>			
((ii) Neat diagrams must	be drawn whereve	er necessary.			
(1	iii) Figures to the right	side indicate full	marks.			
(iv) Use of calculator is	allowed.				
	(v) Assume suitable dat	a, if necessary				
1. (<i>a</i>)	Write a short note on	vapour pressure.	[2]			
(b)	Define Newtonian and	non-Newtonian flui	ids and give <i>two</i>			
	examples of each.		S [.] [3]			
		Dr	2, 201			
2. (<i>a</i>)	Define the following pro		their units : [3]			
	(<i>i</i>) Bulk modulus of e	elasticity				
	(<i>ii</i>) Specific weight					
5	(<i>iii</i>) Surface tension.					
<i>(b)</i>	State and explain Newt	on's law of viscosi	ty. [2]			
		\searrow	P.T.O.			

3.	(<i>a</i>)	Explain the three states of equilibrium of a floating body with				
		reference to its metacentric height.	[3]			
	(<i>b</i>)	Define Buoyancy, centre of Buoyancy.	[2]			
		Or Or	0			
4.	<i>(a)</i>	State and explain Pascal's law.	[2]			
	(<i>b</i>)	Explain in brief–Pressure Transducers.	[3]			
5.	(<i>a</i>)	$u = x^2 + y^2 + 2z^2$, $v = -x^2y - yz - xy$, find ω to satisfy				
		continuity.	[3]			
	(<i>b</i>)	Define path line and streak line and give the example of each.				
			[2]			
		Or Cor				
6.	<i>(a)</i>	Obtain a stream function to the following velocity components,				
		u = x + y, and $v = x - y$.	[3]			
	(<i>b</i>)	Define :	[2]			
		(i) Steady and unsteady flow,				
		(ii) Uniform and non-uniform flow.	3			
		D. r. B. r.				
7.	(<i>a</i>)	What is an orifice ? State the <i>two</i> differences between				
		Orificemeter and Venturimeter. [2]				
	(<i>b</i>)	Draw a neat sketch of Rotameter and explain its working	; in			
		brief.	[3]			
		Or Or				
8.	(<i>a</i>)	List out the assumptions of Bernoulli's equation.	[3]			
	(<i>b</i>)	What do you understand by dynamics of fluid flow ? H	Iow			
		does it differ from kinematics of fluid flow ? [2]				
[5959	1-506	9				

[5252]-506

5

- What is laminar sub-layer ? How is its existence established? [4] 9. (a)
 - *(b)* Derive expression for boundary layer thickness, boundary shear stress and friction drag in a turbulent boundary layer. [6]
 - (*c*) A fluid of viscosity 0.8 N-s/m² and specific gravity 1.2 is flowing through a circular pipe of diameter 100 mm. The maximum shear stress at the pipe wall is given as 200.2 N/m². Find : (a) \bigcirc The pressure gradient The average velocity (b)Reynold's number of the flow. [5]
- Define momentum thickness and derive an expression for the 10. (a)[5] same.

Or

(b) For a steady laminar flow in a horizontal circular pipe derive expression for [5]

(i) Shear stress,

(*ii*) The pressure drop.

- A laminar flow of oil of absolute viscosity 0.20 N-s/m² and (c)density 900 kg/m³ flows through a pipe of diameter of 9.40.10.20 0.35 m. If the head loss of 25m is observed in a length of 2500 m, determine : [5]
 - The velocity of flow, (i)
 - Reynold's number, (ii)
 - Friction factor. (iii)

[5252]-506

P.T.O.

- 11. (a) Three pipes, 300 m long and 300 mm diameter, 150 m long and 20 mm dia., 200 m long and 250 mm dia. are connected in series in same order. Pipe having 300 mm diameter is connected to the reservoir. Water level in the reservoir is 15 m above the centerline of the pipe which is horizontal. The respective friction factor for the pipes are 0.018, 0.02, and 0.019. Determine :
 - (i) Flow rate

(*ii*) Magnitude of loss of head in each pipeThe equivalent diameter of the single replacing the three pipes. [5]

(b) Define minor energy losses and major energy losses in pipe.Enlist various types of minor losses in pipe flow. [4]

[6]

- (c) Write short notes on :
 - (i) Prandtl's mixing length theory
 - (*ii*) Hydrodynamically smooth and rough pipes.

Or

12. (*a*)

A farmer wishes to connect two pipes of different lengths and diameters to a common header supplied with 8×10⁻³ m³/s of water from a pump. One pipe is 100 mm long and 5 cm in diameter. The other pipe is 800 m long. Determine the

[5252]-506

diameter of the second pipe such that both pipes have the same flow rate. Assume the pipes to be laid on level ground and friction coefficient for both pipes as 0.02. Also determine the head loss in meters of water in the pipes. [5]

- (b) Derive Karman-Prandtl equation for velocity distribution in turbulent flow near hydrodynamically smooth boundary. [5]
- (c) Explain with sketches the difference between hydrodynamically smooth and rough boundaries. [5]

[5252]-506

 $\mathbf{5}$