

Total No. of Questions : 6]

SEAT No. :

P5814

[Total No. of Pages : 2

BE/Insem./Oct.-503

B.E. (Civil)

STRUCTURAL DESIGN & DRAWING - III

(2015 Pattern) (Semester - I)

Time : 1.30 Hours]

[Max. Marks : 30

Instructions to the candidates:

- 1) *Answer Q.1 or Q.2, Q.3 or Q.4, Q.5 or Q.6*
- 2) *Neat sketches must drawn wherever necessary.*
- 3) *Figures to right indicate full marks.*
- 4) *Assume suitable data if necessary.*
- 5) *IS 1343:2012, IS 456:2000 are allowed in examination.*
- 6) *Use of electronic pocket calculator is allowed.*
- 7) *Use of cell phone is prohibited during examination.*

Q1) A post tensioned prestressed concrete beam with top flange 750mm × 200mm, web 150mm × 500mm and bottom flange 400mm × 300mm. It is simply supported over a span of 30m and carries a superimposed load of 10kN/m exclusive of self-weight. It is prestressed with 10 numbers of 12/5 Freyssinet cables with their C.G. at 100mm from soffit at midspan section varying linearly with zero eccentricity at ends. Prestress at transfer is 1000 N/mm² and loss ratio 0.85. Calculate extreme fiber stresses at midspan under initial and final conditions. Unit weight of prestressed concrete 25 kN/ m³. **[10]**

OR

Q2) a) Explain Freyssinet system of prestressing. **[4]**
b) A pretension prestressed concrete beam, 200mm wide and 300mm deep, prestressed with wires (area = 320 mm²) located at a constant eccentricity of 50mm and carrying an initial stress of 1000N/mm². The span of the beam is 10m. Calculate the percentage loss of stress in wires $E_s = 210\text{kN/mm}^2$ and $E_c = 35 \text{ kN/mm}^2$. Relaxation of steel stress = 5% of initial stress. Shrinkage of concrete 300×10^{-6} for pretensioning. Creep coefficient = 1.6. Frictional coefficient for wave effect = 0.00 15 per m. **[6]**

Q3) A post tensioned prestressed concrete one way slab is spanning over 8 m, to support an imposed load of 20kN/m. The stresses in concrete should not exceed 19.6 N/mm² in compression and 1.2 N/mm² in tension. Calculate the minimum possible depth and minimum prestressing force required. Also find corresponding eccentricity. **[10]**


P.T.O.

OR

- Q4)** The cross of prestress concrete beam is unsymmetrical T section with following dimension: Overall depth 1600 mm, web 300 mm and flange 1200mm × 300mm. At a particular section the beam is subjected to ultimate moment and shear force of 2400 kNm and 400 kN respectively. Design the beam with following data : [10]

Grade of concrete-M40, effective depth 1200mm, $A_p = 2420 \text{ mm}^2$, $F_p = 1600 \text{ Mpa}$ effective prestress at extreme tensile in the beam is 20.5 Mpa.

- Q5)** Continuous Flat slab with drop for a shopping mall is as shown in figure.1 below. The size of column is 450mm × 450 mm. Use M30 grade of concrete and Fe415 steel. Calculate total design moments for S1 as shown in below figure. Take LL= 4 kN/m² and FFL = 1.0kN/m². [10]



OR

- Q6)** a) Briefly outline the salient design features of continuous prestressed concrete flat slab. [6]
b) What is the necessary two way shear in flat slab [4]

