Total No. of Questions : 6]	8	SEAT No. :
P175		[Total No. of Pages : 2

BE/INSEM/APR-501 B.E. (Civil Engineering)

401007: DAMS AND HYDRAULIC STRUCTURES

(2015 Pattern) (Semester - II)

Time: 1 Hour] [Max. Marks: 30]
Instructions to the candidates:

- 1) Solve Q.1 OR Q.2, Q.3 OR Q.4 and Q.5 OR Q.6.
- 2) Neat sketches/diagrams must be drawn wherever necessary.
- 3) Figures to the right Indicate full marks for the sub-questions.
- 4) Assume suitable data if necessary and state them in your answer clearly.
- 5) Use of non-programmable pocket size electronic calculator is allowed.
- Q1) a) Explain four factors considered for selection of an ideal site for a dam.[4]
 - b) Explain with sketches various types of piezometers (working & uses).[6]
- Q2) a) Explain with sketch/sketches the instrumentation required for monitoring (Measurement of) joints and cracks in a concrete dam. [4]
 - b) i) Discuss the displacement and rehabilitation issues with reference to a big dam project.
 - ii) State three differences between overflow and non-overflow types of dams with the help of neat sketches.

[3 + 3]


Q3) a) Discuss briefly 4 site conditions those are most suitable for an arch dam.

[4]

b) For the dam section shown, *check the stability of dam in overturning*.

Use the data given below.

[6]



P.T.O.

- Specific weights of concrete and water are 24 kN/m³ and 10 kN/m³ respectively; F.S. = 1.50 for overturning.
- Consider only hydrostatic force, weight of water and uplift forces only (Neglect wind/ wave and seismic forces).
- There is no gallery and no tail-water.

- What is meant by 'elementary profile of gravity dam'? Draw an *Q4*) a) explanatory sketch. Using relevant formulas and assuming necessary values; show that maximum height of a small gravity dam is 88m.
 - What is mean by an arch dam? Give classification of arch dams. Show b) these types in neat sketches.
- If Froude's Numbers (Fr) is 3.9; describe the specific type of Indian **Q5**) a) Standard stilling basin (IS 4997-1968) for energy dissipation below spillway along with sketch. [4]
 - b) Discuss the following clearly with respect to spillway crest gates:[3+3]
 - Inspection of gates. i)
 - Maintenance of gates ii)

- Show sectional elevation and plan of a vertical lift (Sliding) gate provided **Q6**) a) for a spillway. Briefly explain its working.
 - An ogee spillway is to be designed for a discharge of 20 m³/s with b) upstream face vertical and downstream face having slope 1V: 0.8H. Obtain the downstream profile of spillway with 1 m interval for the 'x' coordinates in the profile equation $x^{1.85} = 2.y.H^{0.85}$

Assume C = 2.20 and L = 1 m. Neglect effects of end contractions and 2 .0.748.76.73 velocity of approach. **[6]**