Total No.	. of Questions : 8]	SEAT No.:					
PD-405	53	[Total	No. of Pages : 3				
		[1000]	110. 01 1 ages . e				
[6402]-12							
S.E. (Electrical)							
Material Science							
(2019 course) (Semester - III) (203142)							
<i>Time</i> : 2 ¹ /	1/2 Hours]	[M	ax. Marks : 70				
Instructio	ions to the candidate:						
1)	Answer Q1 or Q2, Q3 or Q4, Q5 or Q6, Q	27 or Q8.					
2)	2) Figures to the right side indicate full marks.						
3)	3) Assume Suitable data if necessary.						
<i>4</i>)	Neat diagrams must be drawn wherever	· necessary.					
Q1) a) Classify solid insulating materials according to the temperature ranges. Hence write properties and applications of any two materials from Class							
	A type.		[6]				
b)	State the properties and applications of	of -	[6]				
	i) Air	Transformer oil					
c)	Explain properties of insulating mater	ials which are used	in Cables and				
	Transformers.		[5]				
	OR OR						
Q2) a)	Classify insulating materials and hence		nd applications				
	of any two materials from Class F typ	e.	[6]				
b)	b) Explain properties of insulating materials which are used in Capacitor						
^	and Rotating Machines.	(2) (6)	[5]				
c)	State the properties and applications of		[6]				
	i) Sulphur Hexa Fluoride ii)	Askarel					
		9.	n m A				
		×	<i>P.T.O.</i>				

<i>Q3</i>)	a)	Define with units—	[6]
		i) Magnetic dipole moment ii) Magnetizatio	n
		iii) Magnetic susceptibility	6
	b)	With necessary diagram, classify magnetic material magnetic dipole moment and magnetic susceptibility.	ls on the basis of [6]
	c)	What is Curie temperature? Explain Ferro-magnetic Critical temperature.	behaviour below [6]
		OR OR	V
Q4)	a)	Draw and explain magnetization curve for a ferromaghence define with units - i) Coercive force ii) Saturation.	netic material and [6]
	b)	In a magnetic material, hysteresis loss is 150W when may of 1.3 tesla and frequency is 50Hz. What would be hystensity is decreased to 0.8 tesla and frequency is inc. Assume that hysteresis loss is proportional to $(B_m)^{1.7}$.	steresis loss if flux
	c)	Differentiate Soft Magnetic Materials and Hard Magne	etic Materials. [6]
Q5)	a)	With the neat diagram, explain principle of working Give its examples along with the temperature ranges.	of thermocouple. [6]
	b)	A filament of a 230V lamp is to be drawn from a wire of of 0.025mm and resistivity at 28°C is $5.65 \times 10^{-6} \Omega$ cn temperature coefficient at 28°C is 5×10^{-3} / °C. Calculate filament to dissipate 40W at filament temperature of at	n. If the resistance te the length of the
	c)	State and write properties of electrical carbon mater used for Lamp Filaments.	
[64	02]-	12	

		OR ^		
Q6)	a)	With the neat diagram, explain principle of working of thermal bim Give its examples and applications.	etal. [6]	
	b)	State and write properties of materials used for solders and mater used for different types of fuses.		
	c)	Describe properties and applications of Constantan and Brass.	[6]	
Q 7)	a)	Explain with neat diagram - Single Electron Transistor (SET).	[6]	
	b)	Describe with neat diagrams - Boron Nano Tubes	[6]	
	c)	Explain Nano materials used in Batteries and Photovoltaic Cells	[6]	
		OR CERTIFICATION OF THE PROPERTY OF THE PROPER		
Q 8)	a)	Describe with neat diagram - Nano wires	[6]	
	b)	Describe with neat diagrams - Carbon clusters	[6]	
	c)	Write a short note on - C	[6]	
		ASIAN PA		
	.<			
		80.7		

[6402]-12