

Total No. of Questions : 9]

SEAT No. :

PB3587

[6260]-2

[Total No. of Pages : 4

F.E. (Common)

ENGINEERING PHYSICS

(2019 Credit Pattern) (Semester - I/II) (107002)

Time : 2½ Hours]

[Max. Marks : 70

Instructions to the candidates:

- 1) Q. 1 is compulsory. Answer Q2 or Q3, Q4 or Q5, Q6 or Q7, Q8 or Q9.
- 2) Figures to the right indicate full marks.
- 3) Neat diagram must be drawn wherever necessary.
- 4) Use of non-programmable Electronic pocket calculator is allowed.
- 5) Assume suitable data, if necessary.

Physical Constants:

- Planck's constant, $h = 6.63 \times 10^{-34}$ J.S
- Mass of electron, $m_e = 9.1 \times 10^{-31}$ kg
- Charge on electron = 1.6×10^{-19} C

Q1) Write the correct option with answers for the following questions (1mark each)

[10]

- a) De Broglie wavelength for matter waves associated with a matter particle is _____ its Energy.
 - i) Inversely proportional to square of
 - ii) Directly proportional to
 - iii) Inversely proportional to the square root of
 - iv) Directly proportional to the square root of
- b) A well behaved wave function satisfies which mathematical conditions.
 - i) Finite
 - ii) Single valued
 - iii) Normalizable
 - iv) All of the above
- c) According to Heisenberg Uncertainty principle, in a narrow wave packet of de Broglie wavelength _____ of a particle can be predicted correctly.
 - i) Position
 - ii) Momentum
 - iii) Position and momentum both
 - iv) Neither position nor momentum

P.T.O.

- d) At absolute zero ($T = 0 \text{ K}$), a semiconductor would be
- Perfect semiconductor
 - Insulator
 - Conductor
 - Intrinsic semiconductor
- e) The Hall effect is true for
- Semiconductors only and not metals
 - Metals only and not semiconductors
 - Both metals and semiconductors
 - Insulators
- f) The relation between magnetization (M), susceptibility (χ) and Magnetic field strength (H) is
- $\chi = M \times H$
 - $\chi = H/M$
 - $\chi = M+H$
 - $\chi = M/H$
- g) The relation between magnetic induction (B), Magnetic flux (ϕ), area (A) and is
- $\phi = B/A$
 - $\phi = BA$
 - $\phi = B - A$
 - $\phi = A/B$
- h) The expulsion of magnetic flux from within the superconductor below Critical temperature is known as
- Magnetic effect
 - Expulsion effect
 - Meissner effect
 - Josephson effect
- i) X rays or gamma rays are used in radiography testing technique due to which of their property.
- High frequency
 - High wavelength
 - High velocity
 - Low frequency
- j) A quantum dot (nanoparticle) has all dimensions in the range of
- 100 nm to $1 \mu\text{m}$
 - 1 - 100 nm
 - $1 \mu\text{m}$ to $100 \mu\text{m}$
 - $100 \mu\text{m}$ and above

- Q2)** a) Derive Schrodinger's time independent equation. [6]
 b) What is the Heisenberg uncertainty Principle/ Explain it using narrow and broad wave packets. [5]
 c) The lowest energy of an electron trapped in a potential well is 4.2 eV. Determine the width of the potential well in AU. [4]

OR

- Q3)** a) For a particle enclosed in a rigid box of infinite potential well, derive the equation for energy of the particle. Why is this energy quantized? [6]
 b) What is the de Broglie hypothesis? Explain in brief properties of matter waves (any four). [5]
 c) An electron is confined to a potential well of length 1.5 AU. Calculate the minimum uncertainty in its velocity (assume product of uncertainties equal to 'h'). [4]

- Q4)** a) With a neat and labeled diagram explain the Hall effect. Derive expression for Hall voltage. [6]
 b) Define Fermi level for a semiconductor. Draw a neat and labeled energy diagram for a PN junction diode showing Fermi levels when it is in
 (i) Zero bias (equilibrium)
 (ii) Forward bias [5]
 c) A sample of intrinsic germanium has a carrier concentration of $4.41 \times 10^{22} / \text{cm}^3$. If the donor impurity is added in the ratio 1:10⁷ atoms / cm³, determine resistivity of the sample. [Given, mobility of electrons, $\mu_e = 3800 \text{ cm}^2/\text{V.s}$.] [4]

OR

- Q5)** a) Derive the expression for electrical conductivity of a semiconductor. Discuss how this equation is modified for intrinsic, N-type and p-type semiconductors. [6]
 b) Define efficiency of solar cell. Explain any four ways by which the efficiency of solar cell can be improved. [5]
 c) An n-type semiconductor has a thickness of 0.15 mm and a current of 1mA is flowing along its length. Calculate Hall voltage developed along its width if a magnetic field of 2T is applied perpendicular to its thickness. [Hall coefficient, $R_H = 3.68 \times 10^{-4} \text{ m}^3/\text{C}$.] [4]

- Q6)** a) Differentiate between diamagnetic, paramagnetic and ferromagnetic materials. (Any three points). [6]
- b) What is super conductivity? Explain any two applications of superconductors in brief. [5]
- c) For Lead, the critical magnetic field at 0K, $H_c(0)$ is 8×10^5 A/m. and it has a transition temperature (T_c) of 7.26 K. In a certain application, Lead has to be used as a superconductor subjected to a magnetic field of $H_c(T) = 4 \times 10^4$ A/m. At what maximum temperature it can be operated? [4]

OR

- Q7)** a) What is the Meissner effect? Discuss the reason why it is observed? Show that superconductors exhibit perfect diamagnetism below the critical temperature. [6]
- b) Explain the process of recording and retrieving (reading) data in magnetic storage devices. [5]
- c) Explain brief:
- Magnetic Susceptibility (χ)
 - Absolute permeability (μ)
- [4]
- Q8)** a) What is echo sounding? Using this technique, explain how ultrasonic waves can be used for flaw detection. [6]
- b) What is quantum confinement? On its basis explain why nanoparticles exhibit different properties than corresponding bulk materials. [5]
- c) State applications of nanotechnology in the field of electronics (any four). Explain any one application in brief. [4]

OR

- Q9)** a) Explain optical and electrical properties of nanoparticles. [6]
- b) State the objectives of Non-Destructive Testing. Differentiate between destructive and non-destructive testing (any two points). [5]
- c) An ultrasonic pulse of frequency 100 kHz is sent through a block of aluminum with velocity 6320 m/s and. The echo is recorded after 1.45 microseconds. Calculate the thickness of the block and the wavelength of the ultrasonic pulse. [4]